

## ■ Insulated pipe clamp Husky II 13 6 mm Insulation 12 M8



### Commercial details

Part no.	6830060
EAN/GTIN	4250928440341
Packing unit	24 pcs
Quantity unit	pcs
Weight	0,0344 kg/pc
Product group	06-683
Price unit	1

### QR code



### Certification



### Specification

Application area	A thermal decoupled mounting of tubes guarantees a reliable prevention of condensate for refrigeration, air-conditioning and drinking water technologies in the sector pipe-clamping.
Insulation body	KA/PU

### Technical data

Material	Steel
Material type	DD11
Material coat	Plastic
Surface	galvanized
Corrosion category	C2 very high
Surrounding area	Indoor area
Class	B2
min. temperature resistance	-45 °C
max. temperature resistance	105 °C
Thermal conductivity	0,029 W/mK
Density shell	120 kg/m <sup>3</sup>
Water vapour diffusion resistance	20000 μ

### Product details

Connection	M8
Connection height A	22 mm
Width B	56 mm
Insulation thickness	12 mm
Load F <sub>z</sub>	0,04 kN
Length shell L	36 mm
Statical load shell	0,27 N/mm <sup>2</sup>

### Remark

Notice exchange and returns are excluded. Special design on request.