


■ Insulated pipe clamp RG80s ALU/PU 48,3 mm Insulation 20 x 50 mm M8/M10



Commercial details

Part no.	70504849
EAN/GTIN	4250928441287
Packing unit	1 pcs
Quantity unit	pcs
Weight	0,154 kg/pc
Product group	06-705
Price unit	1

QR code



Certification



Specification

Application area	A thermal decoupled mounting of tubes guarantees a reliable prevention of condensate for refrigeration, air-conditioning and drinking water technologies in the sector pipe-clamping
Insulation body	ALU/PU

Technical data

Material	Steel
Material type	DD11
Material coat	Aluminum foil
Surface	galvanized
Class	B2
min. temperature resistance	-50 °C
max. temperature resistance	120 °C
Thermal conductivity	0,025 W/mK
Density shell	80 kg/m³
Density coat	2700 kg/m³
Thicknes coat	0,08 mm
Water vapour diffusion resistance	18750 µ

Product details

Connection	M8/M10
Connection height A	39 mm
Width B	124 mm
Insulation thickness	20 mm
load Fz	0,3 kN
Length shell L	50 mm
statical load shell	0,1 N/mm²

Remark

Delivery time	5 working days, ex works
Notice	exchange and returns are excluded.

