




■ Sliding sledge A HV 100-150 50x5 450 mm EPDM hot-dip galv.



Commercial details

Part no.	142afb0450
EAN/GTIN	4250928462947
Packing unit	1 pcs
Quantity unit	pcs
Weight	19,31 kg/pc
Product group	14-143
Price unit	1

QR code



Specification

Specification	Double-L-support
Closure	Nut / closure screw

Technical data

Material	Steel
Material type	S235
Surface	hot-dip galvanized
Corrosion category	C4 high / C5 medium
Surrounding area	Indoor and outdoor areas
Sound insulation lining	Rubber EPDM
Safety factor	1,54
min. temperature resistance	-35 °C
max. temperature resistance	100 °C

Product details

Closure screw	M12
Outer pipe diameter	450 mm
Material thickness	8 mm
Width pipe clamp strap	50 mm
Width substructure	341 mm
Length of substructure	270 mm
Load F _x	7,21 kN
Load F _y	5 kN
Load F _z hanging μ 0,2	15,15 kN
Load F _z hanging μ 0,3	15,15 kN

Product details

Load F _Z standing μ 0,2	25 kN
Load F _Z standing μ 0,3	16,67 kN
Thickness clamp strap	5 mm
min. height base	100 mm
max. height base	155 mm
Insulation thickness	6 mm