



■ Profile rail C-profile Stex 35 / 35 / 1 mm L= 2 m pre-galv.



Commercial details

Part no.	1273538
EAN/GTIN	4250928424433
Packing unit	12 m
Bundle	252 m
Quantity unit	m
Weight	1,03 kg/m
Product group	02-127
Price unit	1

QR code



Certification



Specification

Application area	lightweight profile rail with quick connection option.
Specification	Marking for fit-up aid and to cut rails
Type of attachment	glide fast connection

Technical data

Material	Steel
Material type	S250
Surface	pre-galvanized

Product details

Width	35 mm
Height	35 mm
Thickness	1 mm
Length	2 m
Hole-Ø	8,5 mm
Hole diameter 1	8,5 mm
Hole diameter 2	10,5 mm
Elongated hole	8,5x15 mm
Area (least cross section of the profile rail)	1,03 cm ²
Axial angular impulse I_y	1,86 cm ⁴
Axial angular impulse I_z	2,21 cm ⁴
Grid dimension	25 mm
Rail slot width	21 mm
Centroid distance e_o	1,72 cm
Centroid distance e_u	1,78 cm

Remark

Notice	Full bundles, only
Elastic limit	250 N/mm ²
Radius of inertia i_y	1,34 cm
Radius of inertia i_z	1,46 cm
Section modulus W_y	1,04 cm ³
Section modulus W_z	1,26 cm ³